



STREET SIGN SPECIFICATIONS

MATERIAL

- TELESPAR QUICK PUNCH 10' AND 12' POST
- 48" x 2 1/4" x 2 1/4" x 12ga. ANCHOR ASSEMBLY
- 2 1/2" x 2 1/2" x 18" x 12ga. OMNI SLEEVE AT ALL STOP SIGN AND STREET BLADE INSTALLATIONS
- 2 1/2" x 2 1/2" x 18" x 12ga. SLEEVE AT ALL ANCHOR ASSEMBLIES MID BLOCK SIGNS AND IN STABLE SOILS
- 10' x 2' x 2' x 14ga. POST AT ALL MID BLOCK AND SINGLE SIGN INSTALLATIONS
- 12' x 2' x 2' x 14ga. POST AT ALL STOP AND STREET BLADE INSTALLATIONS
- STREET BLADE 3/8" HOLE PUNCH IN CENTER FOR TELESPAR POST AND CENTER ENDS FOR CHERRYMATE RIVET
- STREET BLADES ALUMINUM .080 9" HIGH WITH DG3 GREEN FILM WITH WHITE TEXT. 6" LETTERS AND NUMBERS STARTING WITH CAPITAL LETTER AND THEN LOWER CASE
- ALL POSTS CAPPED WITH 2" PYRAMID AND TELESPAR HARDWARE TO BE USED



STREET NAME SIGN POST
DETAIL

PLATE NO. LV-ST-16

DATE 01/2020